



12" PAPER SUBWOOFER

- LONG THROW HIGH POWER LOADING DESIGN( $X_{max}=12\text{mm}$ )
- EXTREMELY LINEAR EXCURSION DESIGN
- PAPER CONE WITH TWIN ROLL RUBBER SURROUND
- STAMPED STEEL BASKET, CONEY SPIDER
- SUITABLE FOR SUBWOOFER APPLICATION
- VENTED POLE PIECE
- MAGNETIC VOICE COIL

DIAPHRAGM MTL	Air Dry Paper
SURROUND MTL	Rubber W Shape
NOMINAL IMPEDANCE	4 W
DCR IMPEDANCE	3.2 W
SENSITIVITY 1W/1m	90 dB
FREQUENCY RESPONSE	23-1.3K Hz
FREE AIR RESONANCE	23 Hz
VOICE COIL DIAMETER	50 mm
AIR GAP HEIGHT	8 mm
RATED POWER INPUT	300 W
MAXIMUM POWER INPUT	600 W
FORCE FACTOR, BL	14.39 TM
MAGNET WEIGHT (66oz)	1860 g
MOVING MASS	124 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	362.4 MN <sup>-1</sup>
EFFEC.PISTON AREA	0.05 M <sup>2</sup>
Levc	2.8277mH
Zo	64.2465 ohm
X-max	12 mm
Vas	128.6 Litr.
Qts	0.27
Qms	5.46

